




FAG

51238-MP

Axial deep groove ball bearing

Axial deep groove ball bearing 512...-MP,
single direction, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	190 mm	Inner diameter shaft washer
D	270 mm	Outer diameter housing washer
T	62 mm	Height
C _a	335.000 N	Basic dynamic load rating, axial
C _{0a}	1.170.000 N	Basic static load rating, axial
C _{ua}	35.500 N	Fatigue load limit, axial
n _G	1.540 1/min	Limiting speed
n _{gr}	2.010 1/min	Reference speed

Mounting dimensions

d _{a min}	238 mm	Minimum diameter shaft shoulder
D _{a max}	222 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum filled radius



Dimensions

r _{min}	2 mm	Minimum chamfer dimension
D ₁	194 mm	Inner diameter housing washer
d ₁	265 mm	Outer diameter shaft washer

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

A	7,2	Minimum load factor
---	-----	---------------------

Właściwości

-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia