




FAG

51334-MP

Axial deep groove ball bearing

Axial deep groove ball bearing 513...-MP,
single direction, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	170 mm	Inner diameter shaft washer
D	280 mm	Outer diameter housing washer
T	87 mm	Height
C _a	440.000 N	Basic dynamic load rating, axial
C _{0a}	1.560.000 N	Basic static load rating, axial
C _{ua}	47.500 N	Fatigue load limit, axial
n _G	1.220 1/min	Limiting speed
n _{gr}	2.170 1/min	Reference speed

Mounting dimensions

d _{a min}	236 mm	Minimum diameter shaft shoulder
D _{a max}	214 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum filled radius



Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	174 mm	Inner diameter housing washer
d ₁	275 mm	Outer diameter shaft washer

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

A	13	Minimum load factor
---	----	---------------------

Właściwości

- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia