



FAG



53224

Axial deep groove ball bearing

Axial deep groove ball bearing 532, single direction, with spherical housing washer, steel sheet metal cage



Informacje techniczne



Twoja aktualna wersja produktu

Cage	JP	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	120 mm	Inner diameter shaft washer
D	170 mm	Outer diameter housing washer
T	40,8 mm	Height
C _a	128.000 N	Basic dynamic load rating, axial
C _{0a}	385.000 N	Basic static load rating, axial
C _{ua}	14.600 N	Fatigue load limit, axial
n _G	2.550 1/min	Limiting speed
n _{gr}	3.000 1/min	Reference speed
m	2,577 kg	Masa

Mounting dimensions

d _{a min}	150 mm	Minimum diameter shaft shoulder
D _{a max}	145 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum filled radius



Dimensions

r_{min}	1,1 mm	Minimum chamfer dimension
D_1	123 mm	Inner diameter housing washer
d_1	170 mm	Outer diameter shaft washer
R	125 mm	Radius spherical housing washer
A	61 mm	Distance of the center point
T_1	46 mm	Height with seat washer
D_2	145 mm	Bore diameter seat washer
D_3	175 mm	Outside diameter seat washer
C	15 mm	Height seat washer

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Calculation factors

A	0,94	Minimum load factor
-----	------	---------------------

Additional information

U224	Seat washer
------	-------------

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna