



FAG




53236-MP

Axial deep groove ball bearing

Axial deep groove ball bearing 532...-MP,
single direction, with spherical housing
washer, solid brass cage



Informacje techniczne



Twoja aktualna wersja produktu

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	180 mm	Inner diameter shaft washer
D	250 mm	Outer diameter housing washer
T	58,2 mm	Height
C _a	305.000 N	Basic dynamic load rating, axial
C _{0a}	1.030.000 N	Basic static load rating, axial
C _{ua}	32.500 N	Fatigue load limit, axial
n _G	1.670 1/min	Limiting speed
n _{gr}	2.080 1/min	Reference speed
m	8,19 kg	Masa

Mounting dimensions

d _{a min}	222 mm	Minimum diameter shaft shoulder
D _{a max}	210 mm	Maximum diameter of housing shoulder
r _{a max}	1,5 mm	Maximum filled radius



Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
D ₁	183 mm	Inner diameter housing washer
d ₁	245 mm	Outer diameter shaft washer
R	200 mm	Radius spherical housing washer
A	112 mm	Distance of the center point
T ₁	66 mm	Height with seat washer
D ₂	210 mm	Bore diameter seat washer
D ₃	260 mm	Outside diameter seat washer
C	21,5 mm	Height seat washer

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

A	5,4	Minimum load factor
---	-----	---------------------

Additional information

U236	Seat washer
------	-------------

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna