



FAG



53312

Axial deep groove ball bearing

Axial deep groove ball bearing 533, single direction, with spherical housing washer, steel sheet metal cage



Informacje techniczne



Twoja aktualna wersja produktu


Cage	JP	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	60 mm	Inner diameter shaft washer
D	110 mm	Outer diameter housing washer
T	38,3 mm	Height
C _a	101.000 N	Basic dynamic load rating, axial
C _{0a}	207.000 N	Basic static load rating, axial
C _{ua}	9.500 N	Fatigue load limit, axial
n _G	3.150 1/min	Limiting speed
n _{gr}	5.700 1/min	Reference speed
≈m	1,372 kg	Masa

Mounting dimensions

d _{a min}	90 mm	Minimum diameter shaft shoulder
D _{a max}	85 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum filled radius



Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
D ₁	62 mm	Inner diameter housing washer
d ₁	110 mm	Outer diameter shaft washer
R	90 mm	Radius spherical housing washer
A	41 mm	Distance of the center point
T ₁	42 mm	Height with seat washer
D ₂	85 mm	Bore diameter seat washer
D ₃	115 mm	Outside diameter seat washer
C	11,5 mm	Height seat washer

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Calculation factors

A	0,28	Minimum load factor
---	------	---------------------

Additional information

U312	Seat washer
------	-------------

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna