



FAG




53330-MP

Axial deep groove ball bearing

Axial deep groove ball bearing 533...-MP, single direction, with spherical housing washer, solid brass cage



Informacje techniczne



Twoja aktualna wersja produktu


Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	150 mm	Inner diameter shaft washer
D	250 mm	Outer diameter housing washer
T	83,7 mm	Height
C _a	395.000 N	Basic dynamic load rating, axial
C _{0a}	1.330.000 N	Basic static load rating, axial
C _{ua}	43.000 N	Fatigue load limit, axial
n _G	1.340 1/min	Limiting speed
n _{gr}	2.480 1/min	Reference speed
m	15,706 kg	Masa

Mounting dimensions

d _{a min}	210 mm	Minimum diameter shaft shoulder
D _{a max}	200 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum filled radius



Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
D_1	154 mm	Inner diameter housing washer
d_1	245 mm	Outer diameter shaft washer
R	200 mm	Radius spherical housing washer
A	89,5 mm	Distance of the center point
T_1	92 mm	Height with seat washer
D_2	200 mm	Bore diameter seat washer
D_3	260 mm	Outside diameter seat washer
C	26 mm	Height seat washer

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

A	9,3	Minimum load factor
-----	-----	---------------------

Additional information

U330	Seat washer
------	-------------

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna