




FAG

6004-H-2RSR-C3>N

Deep groove ball bearing

Deep groove ball bearing 60...-H-2RSR, single row, H-Series, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |                    |                                         |
|----------------------------------|--------------------|-----------------------------------------|
| Version code                     | >N                 | Not marked on bearing                   |
| Changed internal design          | H                  | Design variant H (H-Series)             |
| Sealing                          | 2RSR               | Contact seal on both sides              |
| Cage                             | JN                 | Steel sheet metal                       |
| Tolerance class                  | PN                 | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | SN                 | Rings dimensional stabilized up to 120° |
| Lubricant                        | Lubricating grease |                                         |
| Radial internal clearance        | C3 (Group 3)       | Internal clearance larger than CN       |
| Bore type                        | Z                  | Cylindrical                             |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 20 mm       | Bore diameter                     |
| D               | 42 mm       | Outside diameter                  |
| B               | 12 mm       | Width                             |
| C <sub>r</sub>  | 9.380 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 5.030 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 300 N       | Fatigue load limit, radial        |
| n <sub>G</sub>  | 9.900 1/min | Limiting speed                    |
| ≈m              | 0,071 kg    | Masa                              |



Mounting dimensions

|             |         |                                      |
|-------------|---------|--------------------------------------|
| $d_{a\min}$ | 23,2 mm | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 38,8 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 0,6 mm  | Maximum fillet radius                |

Dimensions

|            |         |                              |
|------------|---------|------------------------------|
| $r_{\min}$ | 0,6 mm  | Minimum chamfer dimension    |
| $D_1$      | 35,1 mm | Shoulder diameter outer ring |
| $D_2$      | 37 mm   | Caliber diameter outer ring  |
| $d_1$      | 26,9 mm | Shoulder diameter inner ring |
| $d_2$      | 25,6 mm | Caliber diameter inner ring  |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -20 °C | Operating temperature min. |
| $T_{\max}$ | 100 °C | Operating temperature max. |

Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 13,8 | Calculation factor |
|-------|------|--------------------|

Właściwości

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|  | Obciążenie promieniowe              |
|  | Obciążenie osiowe jednokierunkowe   |
|  | Obciążenie osiowe dwukierunkowe     |
|  | Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                   |
|  | Uszczelnienie dwustronne            |