



FAG

6007-N

Deep groove ball bearing

Deep groove ball bearing 60...-N, single row, ring groove, steel sheet metal cage



Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Design, bearing outer ring	N	Ring groove for snap ring
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	62 mm	Outside diameter
B	14 mm	Width
C _r	17.000 N	Basic dynamic load rating, radial
C _{0r}	10.300 N	Basic static load rating, radial
C _{ur}	560 N	Fatigue load limit, radial
n _G	16.100 1/min	Limiting speed
n _{gr}	11.700 1/min	Reference speed
≈m	142,21 g	Masa



Mounting dimensions

$d_{a\min}$	39,6 mm	Minimum diameter shaft shoulder
$D_{a\max}$	57,4 mm	Maximum diameter of housing shoulder
$r_{a\max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
D_1	53,1 mm	Shoulder diameter outer ring
D_2	55,4 mm	Caliber diameter outer ring
d_1	43,2 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	14,9	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia