



FAG

6052-M-C3

Deep groove ball bearing

Deep groove ball bearing 60...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	400 mm	Outside diameter
B	65 mm	Width
C _r	310.000 N	Basic dynamic load rating, radial
C _{0r}	405.000 N	Basic static load rating, radial
C _{ur}	14.300 N	Fatigue load limit, radial
n _G	2.750 1/min	Limiting speed
n _{gr}	2.250 1/min	Reference speed
≈m	29,8 kg	Masa



Mounting dimensions

$d_{a\ min}$	274,6 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	385,4 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	4 mm	Minimum chamfer dimension
D_1	357,5 mm	Shoulder diameter outer ring
d_1	304,05 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

f_0	15,7	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe