





FAG

6068-M
Deep groove ball bearing

Deep groove ball bearing 60...-M, single row,
solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	340 mm	Bore diameter
D	520 mm	Outside diameter
B	82 mm	Width
C _r	445.000 N	Basic dynamic load rating, radial
C _{0r}	690.000 N	Basic static load rating, radial
C _{ur}	21.400 N	Fatigue load limit, radial
n _G	2.050 1/min	Limiting speed
n _{gr}	1.630 1/min	Reference speed
≈m	63,2 kg	Masa



Mounting dimensions

$d_{a\ min}$	358 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	502 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	4 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	5 mm	Minimum chamfer dimension
$D_{\ 1}$	469,55 mm	Shoulder diameter outer ring
$d_{\ 1}$	402,2 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

f_0	15,8	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe