



FAG

607-Z-CO7

Deep groove ball bearing

Deep groove ball bearing 60...-Z, single row, shield , steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Logistical code	CO7	-
Sealing	Z	Non-contact shield on one Side
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	7 mm	Bore diameter
D	19 mm	Outside diameter
B	6 mm	Width
C _r	2.800 N	Basic dynamic load rating, radial
C _{0r}	1.060 N	Basic static load rating, radial
C _{ur}	65 N	Fatigue load limit, radial
n _G	53.000 1/min	Limiting speed
n _{gr}	34.500 1/min	Reference speed
≈m	0,007 kg	Masa



Mounting dimensions

$d_{a \min}$	9 mm	Minimum diameter shaft shoulder
$D_{a \max}$	17 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
D_1	15,5 mm	Shoulder diameter outer ring
D_2	16,7 mm	Caliber diameter outer ring
d_1	10,4 mm	Shoulder diameter inner ring
d_2	9,4 mm	Caliber diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	12,4	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Uszczelnienie jednostronne