



FAG

609-HLN

Deep groove ball bearing

Deep groove ball bearing 60, single row, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Logistical code	HLN	-
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	9 mm	Bore diameter
D	24 mm	Outside diameter
B	7 mm	Width
C _r	3.550 N	Basic dynamic load rating, radial
C _{0r}	1.410 N	Basic static load rating, radial
C _{ur}	88 N	Fatigue load limit, radial
n _G	45.500 1/min	Limiting speed
n _{gr}	30.000 1/min	Reference speed
m	0,015 kg	Masa



Mounting dimensions

d a min	11 mm	Minimum diameter shaft shoulder
D a max	22 mm	Maximum diameter of housing shoulder
r a max	0,3 mm	Maximum fillet radius

Dimensions

r min	0,3 mm	Minimum chamfer dimension
D 1	19 mm	Shoulder diameter outer ring
D 2	20,1 mm	Caliber diameter outer ring
d 1	13,2 mm	Shoulder diameter inner ring
d 2	12,2 mm	Caliber diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

f 0	12,8	Calculation factor
-----	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia