



FAG

61864-M-C3

Deep groove ball bearing

Deep groove ball bearing 618...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	320 mm	Bore diameter
D	400 mm	Outside diameter
B	38 mm	Width
C _r	154.000 N	Basic dynamic load rating, radial
C _{0r}	213.000 N	Basic static load rating, radial
C _{ur}	6.500 N	Fatigue load limit, radial
n _G	2.750 1/min	Limiting speed
n _{gr}	1.710 1/min	Reference speed
≈m	11,2 kg	Masa



Mounting dimensions

$d_{a\min}$	330,2 mm	Minimum diameter shaft shoulder
$D_{a\max}$	389,8 mm	Maximum diameter of housing shoulder
$r_{a\max}$	2,1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
D_1	373,75 mm	Shoulder diameter outer ring
d_1	346,95 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	16	Calculation factor
-------	----	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe