



FAG

61909-2RSR-C3

Deep groove ball bearing

Deep groove ball bearing 619..-2RSR, single row, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	45 mm	Bore diameter
D	68 mm	Outside diameter
B	12 mm	Width
C _r	15.000 N	Basic dynamic load rating, radial
C _{0r}	10.900 N	Basic static load rating, radial
C _{ur}	650 N	Fatigue load limit, radial
n _G	5.100 1/min	Limiting speed
m	0,13 kg	Masa

Mounting dimensions

d _{a min}	48,2 mm	Minimum diameter shaft shoulder
D _{a max}	64,8 mm	Maximum diameter of housing shoulder
r _{a max}	0,6 mm	Maximum fillet radius



Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
D_1	60,6 mm	Shoulder diameter outer ring
D_2	62,8 mm	Caliber diameter outer ring
d_1	52,4 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

Calculation factors

f_0	16	Calculation factor
-------	----	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne