



FAG

6200-H-2Z

Deep groove ball bearing

Deep groove ball bearing 62...-H-2Z, single row, H-Series, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |                    |                                         |
|----------------------------------|--------------------|-----------------------------------------|
| Changed internal design          | H                  | Design variant H (H-Series)             |
| Sealing                          | 2Z                 | Non-contact shield on both sides        |
| Cage                             | JN                 | Steel sheet metal                       |
| Tolerance class                  | PN                 | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | SN                 | Rings dimensional stabilized up to 120° |
| Lubricant                        | Lubricating grease |                                         |
| Radial internal clearance        | CN (Group N)       | Normal internal clearance               |
| Bore type                        | Z                  | Cylindrical                             |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 10 mm        | Bore diameter                     |
| D               | 30 mm        | Outside diameter                  |
| B               | 9 mm         | Width                             |
| C <sub>r</sub>  | 5.400 N      | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 2.390 N      | Basic static load rating, radial  |
| C <sub>ur</sub> | 126 N        | Fatigue load limit, radial        |
| n <sub>G</sub>  | 32.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 22.500 1/min | Reference speed                   |
| ≈m              | 0,032 kg     | Masa                              |



Mounting dimensions

|         |         |                                      |
|---------|---------|--------------------------------------|
| d a min | 14,2 mm | Minimum diameter shaft shoulder      |
| D a max | 25,8 mm | Maximum diameter of housing shoulder |
| r a max | 0,6 mm  | Maximum fillet radius                |

Dimensions

|       |         |                              |
|-------|---------|------------------------------|
| r min | 0,6 mm  | Minimum chamfer dimension    |
| D 1   | 24 mm   | Shoulder diameter outer ring |
| D 2   | 25,9 mm | Caliber diameter outer ring  |
| d 1   | 17,1 mm | Shoulder diameter inner ring |
| d 2   | 15,8 mm | Caliber diameter inner ring  |

Temperature range

|       |        |                            |
|-------|--------|----------------------------|
| T min | -20 °C | Operating temperature min. |
| T max | 120 °C | Operating temperature max. |

Calculation factors

|     |      |                    |
|-----|------|--------------------|
| f 0 | 13,2 | Calculation factor |
|-----|------|--------------------|

Właściwości

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|  | Obciążenie promieniowe              |
|  | Obciążenie osiowe jednokierunkowe   |
|  | Obciążenie osiowe dwukierunkowe     |
|  | Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                   |
|  | Uszczelnienie dwustronne            |