



FAG

6206-C-2HRS-L069>V

Deep groove ball bearing

Deep groove ball bearing 62...-C-2HRS, single row, Generation C, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                                                     |
|----------------------------------|--------------|---------------------------------------------------------------------|
| Version code                     | >V           | Not marked on bearing                                               |
| Changed internal design          | C            | GenerationC                                                         |
| Sealing                          | 2HRS         | Contact seal on both sides                                          |
| Cage                             | JN           | Steel sheet metal                                                   |
| Tolerance class                  | P6           | Class 6 (ISO 492:2023)                                              |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120°                             |
| Lubricant                        | L069         | Low noise high-temperature grease, interchangeable with grease L207 |
| Radial internal clearance        | CN (Group N) | Normal internal clearance                                           |
| Bore type                        | Z            | Cylindrical                                                         |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 30 mm        | Bore diameter                     |
| D               | 62 mm        | Outside diameter                  |
| B               | 16 mm        | Width                             |
| C <sub>r</sub>  | 22.000 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 11.300 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 770 N        | Fatigue load limit, radial        |
| n <sub>G</sub>  | 10.200 1/min | Limiting speed                    |
| ≈m              | 0,194 kg     | Masa                              |



Mounting dimensions

|             |         |                                      |
|-------------|---------|--------------------------------------|
| $d_{a\min}$ | 35,6 mm | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 56,4 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 1 mm    | Maximum fillet radius                |

Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 1 mm     | Minimum chamfer dimension    |
| $D_1$      | 52,67 mm | Shoulder diameter outer ring |
| $D_2$      | 54,91 mm | Caliber diameter outer ring  |
| $d_1$      | 39,33 mm | Shoulder diameter inner ring |
| $d_2$      | 37,72 mm | Caliber diameter inner ring  |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 100 °C | Operating temperature max. |

Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 13,8 | Calculation factor |
|-------|------|--------------------|

Właściwości

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|  | Obciążenie promieniowe              |
|  | Obciążenie osiowe jednokierunkowe   |
|  | Obciążenie osiowe dwukierunkowe     |
|  | Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                   |
|  | Uszczelnienie dwustronne            |