



FAG

6208-C-2HRS>V

Deep groove ball bearing

Deep groove ball bearing 62...-C-2HRS, single row, Generation C, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                         |
|----------------------------------|--------------|-----------------------------------------|
| Version code                     | >V           | Not marked on bearing                   |
| Changed internal design          | C            | GenerationC                             |
| Sealing                          | 2HRS         | Contact seal on both sides              |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | P6           | Class 6 (ISO 492:2023)                  |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120° |
| Lubricant                        | GA13         | Ball bearing and insert bearing grease  |
| Radial internal clearance        | CN (Group N) | Normal internal clearance               |
| Bore type                        | Z            | Cylindrical                             |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 40 mm       | Bore diameter                     |
| D               | 80 mm       | Outside diameter                  |
| B               | 18 mm       | Width                             |
| C <sub>r</sub>  | 33.500 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 17.800 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 1.230 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 7.800 1/min | Limiting speed                    |
| ≈m              | 0,358 kg    | Masa                              |



Mounting dimensions

|             |       |                                      |
|-------------|-------|--------------------------------------|
| $d_{a\min}$ | 47 mm | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 73 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 1 mm  | Maximum fillet radius                |

Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 1,1 mm   | Minimum chamfer dimension    |
| $D_1$      | 67,6 mm  | Shoulder diameter outer ring |
| $D_2$      | 70,56 mm | Caliber diameter outer ring  |
| $d_1$      | 51,88 mm | Shoulder diameter inner ring |
| $d_2$      | 49,3 mm  | Caliber diameter inner ring  |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -20 °C | Operating temperature min. |
| $T_{\max}$ | 100 °C | Operating temperature max. |

Calculation factors

|       |    |                    |
|-------|----|--------------------|
| $f_0$ | 14 | Calculation factor |
|-------|----|--------------------|

Właściwości

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|  | Obciążenie promieniowe              |
|  | Obciążenie osiowe jednokierunkowe   |
|  | Obciążenie osiowe dwukierunkowe     |
|  | Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                   |
|  | Uszczelnienie dwustronne            |