



FAG

6211-H-SN

Deep groove ball bearing

Deep groove ball bearing 62...-H, single row,
H-Series, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Changed internal design	H	Design variant H (H-Series)
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	100 mm	Outside diameter
B	21 mm	Width
C _r	39.070 N	Basic dynamic load rating, radial
C _{0r}	26.540 N	Basic static load rating, radial
C _{ur}	1.580 N	Fatigue load limit, radial
n _G	9.600 1/min	Limiting speed
n _{gr}	7.500 1/min	Reference speed
m	0,611 kg	Masa



Mounting dimensions

$d_{a\ min}$	64 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	91 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1,5 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	1,5 mm	Minimum chamfer dimension
D_1	86,1 mm	Shoulder diameter outer ring
d_1	68,9 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Calculation factors

f_0	14,6	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia