



FAG

62206-A-2RSR

Deep groove ball bearing

Deep groove ball bearing 622...-A-2RSR, single row, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |                    |                                         |
|----------------------------------|--------------------|-----------------------------------------|
| Changed internal design          | A                  | Design variant A                        |
| Sealing                          | 2RSR               | Contact seal on both sides              |
| Cage                             | JN                 | Steel sheet metal                       |
| Tolerance class                  | PN                 | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | SN                 | Rings dimensional stabilized up to 120° |
| Lubricant                        | Lubricating grease |                                         |
| Radial internal clearance        | CN (Group N)       | Normal internal clearance               |
| Bore type                        | Z                  | Cylindrical                             |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 30 mm       | Bore diameter                     |
| D               | 62 mm       | Outside diameter                  |
| B               | 20 mm       | Width                             |
| C <sub>r</sub>  | 20.700 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 11.300 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 780 N       | Fatigue load limit, radial        |
| n <sub>G</sub>  | 6.600 1/min | Limiting speed                    |
| ≈m              | 0,25 kg     | Masa                              |



Mounting dimensions

|             |         |                                      |
|-------------|---------|--------------------------------------|
| $d_{a\min}$ | 35,6 mm | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 56,4 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 1 mm    | Maximum fillet radius                |

Dimensions

|            |         |                              |
|------------|---------|------------------------------|
| $r_{\min}$ | 1 mm    | Minimum chamfer dimension    |
| $D_1$      | 51,7 mm | Shoulder diameter outer ring |
| $D_2$      | 55,2 mm | Caliber diameter outer ring  |
| $d_1$      | 40,3 mm | Shoulder diameter inner ring |
| $d_2$      | 38 mm   | Caliber diameter inner ring  |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -20 °C | Operating temperature min. |
| $T_{\max}$ | 100 °C | Operating temperature max. |

Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 13,8 | Calculation factor |
|-------|------|--------------------|

Właściwości

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|  | Obciążenie promieniowe              |
|  | Obciążenie osiowe jednokierunkowe   |
|  | Obciążenie osiowe dwukierunkowe     |
|  | Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                   |
|  | Uszczelnienie dwustronne            |