



FAG

6222-MA-P5-S1-C3

Deep groove ball bearing

Deep groove ball bearing 62...-MA, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	MA	Solid brass cage, outer ring guided
Tolerance class	P5	Class 5 (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width
C _r	153.000 N	Basic dynamic load rating, radial
C _{0r}	117.000 N	Basic static load rating, radial
C _{ur}	6.500 N	Fatigue load limit, radial
n _G	5.800 1/min	Limiting speed
n _{gr}	4.500 1/min	Reference speed
≈m	5,422 kg	Masa



Mounting dimensions

$d_{a\ min}$	122 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	188 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	2,1 mm	Minimum chamfer dimension
D_1	172,25 mm	Shoulder diameter outer ring
d_1	138,42 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

f_0	14,3	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia