



FAG

626-Z-HLN

Deep groove ball bearing

Deep groove ball bearing 62...-Z, single row, shield , steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                         |
|----------------------------------|--------------|-----------------------------------------|
| Logistical code                  | HLN          | -                                       |
| Sealing                          | Z            | Non-contact shield on one Side          |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120° |
| Lubricant                        | Without      | Bearing not greased                     |
| Radial internal clearance        | CN (Group N) | Normal internal clearance               |
| Bore type                        | Z            | Cylindrical                             |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 6 mm         | Bore diameter                     |
| D               | 19 mm        | Outside diameter                  |
| B               | 6 mm         | Width                             |
| C <sub>r</sub>  | 2.800 N      | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 1.060 N      | Basic static load rating, radial  |
| C <sub>ur</sub> | 65 N         | Fatigue load limit, radial        |
| n <sub>G</sub>  | 53.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 30.500 1/min | Reference speed                   |
| ≈m              | 7,24 g       | Masa                              |



Mounting dimensions

|             |         |                                      |
|-------------|---------|--------------------------------------|
| $d_{a\min}$ | 8,4 mm  | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 16,6 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 0,3 mm  | Maximum fillet radius                |

Dimensions

|            |         |                              |
|------------|---------|------------------------------|
| $r_{\min}$ | 0,3 mm  | Minimum chamfer dimension    |
| $D_1$      | 15,5 mm | Shoulder diameter outer ring |
| $D_2$      | 16,7 mm | Caliber diameter outer ring  |
| $d_1$      | 10,4 mm | Shoulder diameter inner ring |
| $d_2$      | 9,4 mm  | Caliber diameter inner ring  |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 12,4 | Calculation factor |
|-------|------|--------------------|

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Uszczelnienie jednostronne        |