



FAG

6303-C-Z>V

Deep groove ball bearing

Deep groove ball bearing 63.-C-Z, single row, Generation C, shield , steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                         |
|----------------------------------|--------------|-----------------------------------------|
| Version code                     | >V           | Not marked on bearing                   |
| Changed internal design          | C            | GenerationC                             |
| Sealing                          | Z            | Non-contact shield on one Side          |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | P6           | Class 6 (ISO 492:2023)                  |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120° |
| Lubricant                        | Without      | Bearing not greased                     |
| Radial internal clearance        | CN (Group N) | Normal internal clearance               |
| Bore type                        | Z            | Cylindrical                             |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 17 mm        | Bore diameter                     |
| D               | 47 mm        | Outside diameter                  |
| B               | 14 mm        | Width                             |
| C <sub>r</sub>  | 15.800 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 6.500 N      | Basic static load rating, radial  |
| C <sub>ur</sub> | 450 N        | Fatigue load limit, radial        |
| n <sub>G</sub>  | 24.500 1/min | Limiting speed                    |
| n <sub>gr</sub> | 17.400 1/min | Reference speed                   |
| ≈m              | 0,111 kg     | Masa                              |



Mounting dimensions

|             |         |                                      |
|-------------|---------|--------------------------------------|
| $d_{a\min}$ | 22,6 mm | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 41,4 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 1 mm    | Maximum fillet radius                |

Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 1 mm     | Minimum chamfer dimension    |
| $D_1$      | 38,14 mm | Shoulder diameter outer ring |
| $D_2$      | 40,07 mm | Caliber diameter outer ring  |
| $d_1$      | 25,93 mm | Shoulder diameter inner ring |
| $d_2$      | 24,77 mm | Caliber diameter inner ring  |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 12,2 | Calculation factor |
|-------|------|--------------------|

Właściwości

|  |                                   |
|--|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Uszczelnienie jednostronne        |