



**FAG****6305-C-C4>V**

Deep groove ball bearing

Deep groove ball bearing 63...-C, single row,  
Generation C, steel sheet metal cage

## Informacje techniczne



## Twoja aktualna wersja produktu

|                                  |              |                                         |
|----------------------------------|--------------|-----------------------------------------|
| Version code                     | >V           | Not marked on bearing                   |
| Changed internal design          | C            | GenerationC                             |
| Sealing                          | Without      | Not sealed                              |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | P6           | Class 6 (ISO 492:2023)                  |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120° |
| Lubricant                        | Without      | Bearing not greased                     |
| Radial internal clearance        | C4 (Group 4) | Internal clearance larger than C3       |
| Bore type                        | Z            | Cylindrical                             |

## Main Dimensions &amp; Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 25 mm        | Bore diameter                     |
| D               | 62 mm        | Outside diameter                  |
| B               | 17 mm        | Width                             |
| C <sub>r</sub>  | 26.500 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 11.500 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 790 N        | Fatigue load limit, radial        |
| n <sub>G</sub>  | 17.800 1/min | Limiting speed                    |
| n <sub>gr</sub> | 13.500 1/min | Reference speed                   |
| ≈m              | 0,207 kg     | Masa                              |



### Mounting dimensions

|              |       |                                      |
|--------------|-------|--------------------------------------|
| $d_{a \min}$ | 32 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 55 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1 mm  | Maximum fillet radius                |

### Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 1,1 mm   | Minimum chamfer dimension    |
| $D_1$      | 51,55 mm | Shoulder diameter outer ring |
| $D_2$      | 53,8 mm  | Caliber diameter outer ring  |
| $d_1$      | 35,45 mm | Shoulder diameter inner ring |
| $d_2$      | 34,12 mm | Caliber diameter inner ring  |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 12,4 | Calculation factor |
|-------|------|--------------------|

### Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |