



FAG

6308-MA-C3

Deep groove ball bearing

Deep groove ball bearing 63...-MA, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                         |
|----------------------------------|--------------|-----------------------------------------|
| Sealing                          | Without      | Not sealed                              |
| Cage                             | MA           | Solid brass cage, outer ring guided     |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120° |
| Lubricant                        | Without      | Bearing not greased                     |
| Radial internal clearance        | C3 (Group 3) | Internal clearance larger than CN       |
| Bore type                        | Z            | Cylindrical                             |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 40 mm        | Bore diameter                     |
| D               | 90 mm        | Outside diameter                  |
| B               | 23 mm        | Width                             |
| C <sub>r</sub>  | 45.500 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 25.000 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 1.690 N      | Fatigue load limit, radial        |
| n <sub>G</sub>  | 14.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 9.000 1/min  | Reference speed                   |
| ≈m              | 0,747 kg     | Masa                              |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a\ min}$ | 49 mm  | Minimum diameter shaft shoulder      |
| $D_{a\ max}$ | 81 mm  | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 1,5 mm | Maximum fillet radius                |

### Dimensions

|             |          |                              |
|-------------|----------|------------------------------|
| $r_{\ min}$ | 1,5 mm   | Minimum chamfer dimension    |
| $D_1$       | 75 mm    | Shoulder diameter outer ring |
| $d_1$       | 55,55 mm | Shoulder diameter inner ring |

### Temperature range

|             |        |                            |
|-------------|--------|----------------------------|
| $T_{\ min}$ | -30 °C | Operating temperature min. |
| $T_{\ max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |    |                    |
|-------|----|--------------------|
| $f_0$ | 13 | Calculation factor |
|-------|----|--------------------|

### Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |