



FAG

6313-C-Z

Deep groove ball bearing

Deep groove ball bearing 63.-C-Z, single row, Generation C, shield , steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Changed internal design	C	GenerationC
Sealing	Z	Non-contact shield on one Side
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	140 mm	Outside diameter
B	33 mm	Width
C _r	101.000 N	Basic dynamic load rating, radial
C _{0r}	60.000 N	Basic static load rating, radial
C _{ur}	4.100 N	Fatigue load limit, radial
n _G	7.300 1/min	Limiting speed
n _{gr}	7.000 1/min	Reference speed
≈m	2,07 kg	Masa



Mounting dimensions

d a min	77 mm	Minimum diameter shaft shoulder
D a max	128 mm	Maximum diameter of housing shoulder
r a max	2,1 mm	Maximum fillet radius

Dimensions

r min	2,1 mm	Minimum chamfer dimension
D 1	118,22 mm	Shoulder diameter outer ring
D 2	121,4 mm	Caliber diameter outer ring
d 1	87,73 mm	Shoulder diameter inner ring
d 2	85,59 mm	Caliber diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Calculation factors

f 0	13,2	Calculation factor
-----	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Uszczelnienie jednostronne