



FAG

6315-M

Deep groove ball bearing

Deep groove ball bearing 63...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	160 mm	Outside diameter
B	37 mm	Width
C _r	123.000 N	Basic dynamic load rating, radial
C _{0r}	77.000 N	Basic static load rating, radial
C _{ur}	4.850 N	Fatigue load limit, radial
n _G	8.200 1/min	Limiting speed
n _{gr}	5.800 1/min	Reference speed
≈m	3,75 kg	Masa



Mounting dimensions

$d_{a\ min}$	87 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	148 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	2,1 mm	Minimum chamfer dimension
D_1	133,34 mm	Shoulder diameter outer ring
d_1	101,77 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	150 °C	Operating temperature max.

Calculation factors

f_0	13,2	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia