



FAG

6320-M-R114-139

Deep groove ball bearing

Deep groove ball bearing 63...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	R\$-\$	Special radial internal clearance in µm
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	215 mm	Outside diameter
B	47 mm	Width
C _r	177.000 N	Basic dynamic load rating, radial
C _{0r}	137.000 N	Basic static load rating, radial
C _{ur}	7.400 N	Fatigue load limit, radial
n _G	5.500 1/min	Limiting speed
n _{gr}	4.600 1/min	Reference speed
≈m	8,65 kg	Masa



Mounting dimensions

$d_{a\min}$	114 mm	Minimum diameter shaft shoulder
$D_{a\max}$	201 mm	Maximum diameter of housing shoulder
$r_{a\max}$	2,5 mm	Maximum fillet radius

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
D_1	179,14 mm	Shoulder diameter outer ring
d_1	138,5 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Calculation factors

f_0	13,7	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia