



FAG

6338-M-R90-117

Deep groove ball bearing

Deep groove ball bearing 63...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	R\$-\$	Special radial internal clearance in µm
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	190 mm	Bore diameter
D	400 mm	Outside diameter
B	78 mm	Width
C _r	380.000 N	Basic dynamic load rating, radial
C _{0r}	455.000 N	Basic static load rating, radial
C _{ur}	18.700 N	Fatigue load limit, radial
n _G	2.850 1/min	Limiting speed
n _{gr}	2.290 1/min	Reference speed
≈m	50,4 kg	Masa



Mounting dimensions

$d_{a\min}$	210 mm	Minimum diameter shaft shoulder
$D_{a\max}$	380 mm	Maximum diameter of housing shoulder
$r_{a\max}$	4 mm	Maximum fillet radius

Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
D_1	334 mm	Shoulder diameter outer ring
d_1	258,15 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	13,9	Calculation factor
-------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe