



FAG

6406-A-C3

Deep groove ball bearing

Deep groove ball bearing 64...-A, single row,
steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Changed internal design	A	Design variant A
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width
C _r	46.000 N	Basic dynamic load rating, radial
C _{0r}	23.900 N	Basic static load rating, radial
C _{ur}	1.350 N	Fatigue load limit, radial
n _G	11.000 1/min	Limiting speed
n _{gr}	9.500 1/min	Reference speed
m	0,721 kg	Masa



Mounting dimensions

$d_{a\ min}$	41 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	79 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1,5 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	1,5 mm	Minimum chamfer dimension
D_1	71,2 mm	Shoulder diameter outer ring
d_1	50,1 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Calculation factors

f_0	12,3	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia