



FAG

682-2Z>N

Deep groove ball bearing

Deep groove ball bearing 68...2Z, single row, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	2 mm	Bore diameter
D	5 mm	Outside diameter
B	2,3 mm	Width
C _r	123 N	Basic dynamic load rating, radial
C _{0r}	27,5 N	Basic static load rating, radial
C _{ur}	1,42 N	Fatigue load limit, radial
n _G	134.000 1/min	Limiting speed
n _{gr}	98.000 1/min	Reference speed
≈m	1 g	Masa



Mounting dimensions

$d_{a\min}$	2,52 mm	Minimum diameter shaft shoulder
$D_{a\max}$	4,48 mm	Maximum diameter of housing shoulder
$r_{a\max}$	0,08 mm	Maximum fillet radius

Dimensions

$r_{\min}$	0,08 mm	Minimum chamfer dimension
D_1	4 mm	Shoulder diameter outer ring
D_2	4,4 mm	Caliber diameter outer ring
d_1	2,9 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	6,2	Calculation factor
-------	-----	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne