



686>N

Deep groove ball bearing

Deep groove ball bearing 68..., single row,
steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	6 mm	Bore diameter
D	13 mm	Outside diameter
B	3,5 mm	Width
C _r	1.150 N	Basic dynamic load rating, radial
C _{0r}	440 N	Basic static load rating, radial
C _{ur}	27 N	Fatigue load limit, radial
n _G	72.000 1/min	Limiting speed
n _{gr}	36.500 1/min	Reference speed
≈m	1,87 g	Masa



Mounting dimensions

$d_{a \min}$	6,8 mm	Minimum diameter shaft shoulder
$D_{a \max}$	12,2 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,15 mm	Maximum fillet radius

Dimensions

$r_{\min}$	0,15 mm	Minimum chamfer dimension
D_1	11,1 mm	Shoulder diameter outer ring
d_1	7,9 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia