



FAG

693-HLC

Deep groove ball bearing

Deep groove ball bearing 69, single row, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Logistical code	HLC	-
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	3 mm	Bore diameter
D	8 mm	Outside diameter
B	3 mm	Width
C _r	580 N	Basic dynamic load rating, radial
C _{0r}	174 N	Basic static load rating, radial
C _{ur}	10,8 N	Fatigue load limit, radial
n _G	105.000 1/min	Limiting speed
n _{gr}	71.000 1/min	Reference speed
≈m	0,6 g	Masa



Mounting dimensions

$d_{a\ min}$	3,8 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	7,2 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,15 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	0,15 mm	Minimum chamfer dimension
D_1	6,4 mm	Shoulder diameter outer ring
d_1	4,1 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Calculation factors

f_0	11,5	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia