



FAG

7006-B-XL-2RS-TVP-UO


Angular contact ball bearing

Angular contact ball bearing 70..-B-XL-2RS-TVP, single row, X-life, seals, plastic cage



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Sealing	2RS	Contact seal on both sides
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UO	Bearing set clearance-free in O or X arrangement
Lubricant	GA14	Ball bearing grease, low noise

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	55 mm	Outside diameter
B	13 mm	Width
C _r	19.900 N	Basic dynamic load rating, radial
C _{0r}	13.400 N	Basic static load rating, radial
C _{ur}	930 N	Fatigue load limit, radial
n _G	6.900 1/min	Limiting speed
≈m	0,113 kg	Masa



Mounting dimensions

d a min	34,6 mm	Minimum diameter of shaft shoulder
D a max	50,4 mm	Maximum diameter of housing shoulder
D b max	51,8 mm	Maximum diameter of housing shoulder
r a max	1 mm	Maximum fillet radius of shaft
r a1 max	0,6 mm	Maximum fillet radius of housing

Dimensions

r min	1 mm	Minimum chamfer dimension
r 1 min	0,6 mm	Minimum chamfer dimension
D 1	47,05 mm	Shoulder diameter on outer ring wide side face
D 2	47,7 mm	Caliber diameter on outer ring wide side face
D 3	51,93 mm	Caliber diameter on outer ring small side face
d 1	41,26 mm	Shoulder diameter on inner ring wide side face
d 2	38,04 mm	Caliber diameter on inner ring wide side face
a	24,9 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T min	-20 °C	Operating temperature min.
T max	100 °C	Operating temperature max.

Additional information

Tol (+)	8 μm	Tolerance for axial clearance or preload per set
A min	0 μm	Axial clearance per set min.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne