



FAG

7056-MP-UA

Angular contact ball bearing

Angular contact ball bearing 70..-MP, single row, solid brass cage



Informacje techniczne

Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UA	Bearing set with small axial internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	420 mm	Outside diameter
B	65 mm	Width
C _r	375.000 N	Basic dynamic load rating, radial
C _{0r}	630.000 N	Basic static load rating, radial
C _{ur}	17.700 N	Fatigue load limit, radial
n _G	2.230 1/min	Limiting speed
n _{gr}	1.520 1/min	Reference speed
m	29,9 kg	Masa



Mounting dimensions

d a min	294,6 mm	Minimum diameter of shaft shoulder
D a max	405,4 mm	Maximum diameter of housing shoulder
D b max	413 mm	Maximum diameter of housing shoulder
r a max	3 mm	Maximum fillet radius of shaft
r a1 max	1,5 mm	Maximum fillet radius of housing

Dimensions

r min	4 mm	Minimum chamfer dimension
r 1 min	1,5 mm	Minimum chamfer dimension
D 1	369,2 mm	Shoulder diameter on outer ring wide side face
d 1	333,7 mm	Shoulder diameter on inner ring wide side face
a	133,5 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

T min	-30 °C	Operating temperature min.
T max	200 °C	Operating temperature max.

Additional information

Tol (+)	16 μm	Tolerance for axial clearance or preload per set
A min	130 μm	Axial clearance per set min.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe