



FAG



X-life

7216-B-XL-JP-UA

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-JP,  
single row, X-life, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                                      |         |                                                 |
|------------------------------------------------------|---------|-------------------------------------------------|
| Design variant                                       | B       | B                                               |
| Sealing                                              | Without | Not sealed                                      |
| Cage                                                 | JP      | Steel sheet metal                               |
| Tolerance class                                      | PN      | Normal (ISO 492:2023)                           |
| Dimensional / heat stabilization                     | S0      | Rings dimensional stabilized up to 150°         |
| Bearing with matched conditions for fitting in pairs | UA      | Bearing set with small axial internal clearance |
| Lubricant                                            | Without | Bearing not greased                             |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 80 mm       | Bore diameter                     |
| D               | 140 mm      | Outside diameter                  |
| B               | 26 mm       | Width                             |
| C <sub>r</sub>  | 85.000 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 72.000 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 4.800 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 6.400 1/min | Limiting speed                    |
| n <sub>gr</sub> | 4.950 1/min | Reference speed                   |
| ≈m              | 1,473 kg    | Masa                              |



Mounting dimensions

|               |          |                                      |
|---------------|----------|--------------------------------------|
| $d_{a\ min}$  | 91 mm    | Minimum diameter of shaft shoulder   |
| $D_{a\ max}$  | 129 mm   | Maximum diameter of housing shoulder |
| $D_{b\ max}$  | 134,4 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$  | 2 mm     | Maximum fillet radius of shaft       |
| $r_{a1\ max}$ | 1 mm     | Maximum fillet radius of housing     |

Dimensions

|              |           |                                                   |
|--------------|-----------|---------------------------------------------------|
| $r_{\ min}$  | 2 mm      | Minimum chamfer dimension                         |
| $r_{1\ min}$ | 1 mm      | Minimum chamfer dimension                         |
| $D_1$        | 117,24 mm | Shoulder diameter on outer ring wide side face    |
| $d_1$        | 102,9 mm  | Shoulder diameter on inner ring wide side face    |
| $a$          | 59,2 mm   | Distance between the apexes of the pressure cones |
| $\alpha$     | 40 °      | Contact angle                                     |

Temperature range

|             |        |                            |
|-------------|--------|----------------------------|
| $T_{\ min}$ | -30 °C | Operating temperature min. |
| $T_{\ max}$ | 150 °C | Operating temperature max. |

Additional information

|             |            |                                                  |
|-------------|------------|--------------------------------------------------|
| $Tol\ (+)$  | 12 $\mu m$ | Tolerance for axial clearance or preload per set |
| $A_{\ min}$ | 50 $\mu m$ | Axial clearance per set min.                     |

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia