



FAG



X-life

7222-B-XL-MP

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-MP,
single row, X-life, solid brass cage

Informacje techniczne

Twoja aktualna wersja produktu

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width
C _r	167.000 N	Basic dynamic load rating, radial
C _{0r}	154.000 N	Basic static load rating, radial
C _{ur}	8.600 N	Fatigue load limit, radial
n _G	5.600 1/min	Limiting speed
n _{gr}	3.950 1/min	Reference speed
≈m	4,99 kg	Masa



Mounting dimensions

$d_{a\ min}$	122 mm	Minimum diameter of shaft shoulder
$D_{a\ max}$	188 mm	Maximum diameter of housing shoulder
$D_{b\ max}$	193 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum fillet radius of shaft
$r_{a1\ max}$	1 mm	Maximum fillet radius of housing

Dimensions

$r_{\ min}$	2,1 mm	Minimum chamfer dimension
$r_{1\ min}$	1,1 mm	Minimum chamfer dimension
D_1	165,7 mm	Shoulder diameter on outer ring wide side face
d_1	144,9 mm	Shoulder diameter on inner ring wide side face
a	84 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia