



FAG



X-life

7226-B-XL-MP-P5-UA

Angular contact ball bearing

Angular contact ball bearing 72...-B-XL-MP, single row, X-life, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P5	Class 5 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UA	Bearing set with small axial internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	230 mm	Outside diameter
B	40 mm	Width
C _r	200.000 N	Basic dynamic load rating, radial
C _{0r}	204.000 N	Basic static load rating, radial
C _{ur}	10.600 N	Fatigue load limit, radial
n _G	4.850 1/min	Limiting speed
n _{gr}	3.350 1/min	Reference speed
m	7,01 kg	Masa



Mounting dimensions

$d_{a\ min}$	144 mm	Minimum diameter of shaft shoulder
$D_{a\ max}$	216 mm	Maximum diameter of housing shoulder
$D_{b\ max}$	223 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,5 mm	Maximum fillet radius of shaft
$r_{a1\ max}$	1 mm	Maximum fillet radius of housing

Dimensions

$r_{\ min}$	3 mm	Minimum chamfer dimension
$r_{1\ min}$	1,1 mm	Minimum chamfer dimension
D_1	191,8 mm	Shoulder diameter on outer ring wide side face
d_1	169,64 mm	Shoulder diameter on inner ring wide side face
a	95,5 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	150 °C	Operating temperature max.

Additional information

Tol (+)	10 µm	Tolerance for axial clearance or preload per set
$A_{\ min}$	60 µm	Axial clearance per set min.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia