



FAG



X-life

7302-B-XL-JP-UO

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-JP,
single row, X-life, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Sealing	Without	Not sealed
Cage	JP	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UO	Bearing set clearance-free in O or X arrangement
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	42 mm	Outside diameter
B	13 mm	Width
C _r	15.100 N	Basic dynamic load rating, radial
C _{0r}	7.200 N	Basic static load rating, radial
C _{ur}	495 N	Fatigue load limit, radial
n _G	24.400 1/min	Limiting speed
n _{gr}	14.200 1/min	Reference speed
≈m	92 g	Masa



Mounting dimensions

$d_{a\ min}$	20,6 mm	Minimum diameter of shaft shoulder
$D_{a\ max}$	36,4 mm	Maximum diameter of housing shoulder
$D_{b\ max}$	37,8 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1 mm	Maximum fillet radius of shaft
$r_{a1\ max}$	0,6 mm	Maximum fillet radius of housing

Dimensions

$r_{\ min}$	1 mm	Minimum chamfer dimension
$r_{1\ min}$	0,6 mm	Minimum chamfer dimension
D_1	31,65 mm	Shoulder diameter on outer ring wide side face
d_1	25,99 mm	Shoulder diameter on inner ring wide side face
a	18,5 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	150 °C	Operating temperature max.

Additional information

$Tol\ (+)$	8 μm	Tolerance for axial clearance or preload per set
$A_{\ min}$	0 μm	Axial clearance per set min.

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia