



FAG


7303-B-XL-TVP-P5

Angular contact ball bearing

Angular contact ball bearing 73...-B-XL-TVP,
single row, X-life, plastic cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Sealing	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P5	Class 5 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	47 mm	Outside diameter
B	14 mm	Width
C _r	18.700 N	Basic dynamic load rating, radial
C _{0r}	9.000 N	Basic static load rating, radial
C _{ur}	620 N	Fatigue load limit, radial
n _G	21.600 1/min	Limiting speed
n _{gr}	12.800 1/min	Reference speed
≈m	0,112 kg	Masa



Mounting dimensions

d _{a min}	22,6 mm	Minimum diameter of shaft shoulder
D _{a max}	41,4 mm	Maximum diameter of housing shoulder
D _{b max}	42,8 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum fillet radius of shaft
r _{a1 max}	0,6 mm	Maximum fillet radius of housing

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
D ₁	35,54 mm	Shoulder diameter on outer ring wide side face
d ₁	29,19 mm	Shoulder diameter on inner ring wide side face
a	20,4 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia