



FAG

7319-B-XL-MP-UB

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-MP, single row, X-life, solid brass cage



X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                                                      |         |                                                           |
|------------------------------------------------------|---------|-----------------------------------------------------------|
| Design variant                                       | B       | B                                                         |
| Sealing                                              | Without | Not sealed                                                |
| Cage                                                 | MP      | Solid brass cage, ball guided                             |
| Tolerance class                                      | PN      | Normal (ISO 492:2023)                                     |
| Dimensional / heat stabilization                     | S0      | Rings dimensional stabilized up to 150°                   |
| Bearing with matched conditions for fitting in pairs | UB      | Bearing set with smaller axial internal clearance than UA |
| Lubricant                                            | Without | Bearing not greased                                       |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 95 mm       | Bore diameter                     |
| D               | 200 mm      | Outside diameter                  |
| B               | 45 mm       | Width                             |
| C <sub>r</sub>  | 189.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 167.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 9.600 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 5.700 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3.800 1/min | Reference speed                   |
| m               | 6,495 kg    | Masa                              |



Mounting dimensions

|               |        |                                      |
|---------------|--------|--------------------------------------|
| $d_{a\ min}$  | 109 mm | Minimum diameter of shaft shoulder   |
| $D_{a\ max}$  | 186 mm | Maximum diameter of housing shoulder |
| $D_{b\ max}$  | 193 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$  | 2,5 mm | Maximum fillet radius of shaft       |
| $r_{a1\ max}$ | 1 mm   | Maximum fillet radius of housing     |

Dimensions

|              |           |                                                   |
|--------------|-----------|---------------------------------------------------|
| $r_{\ min}$  | 3 mm      | Minimum chamfer dimension                         |
| $r_{1\ min}$ | 1,1 mm    | Minimum chamfer dimension                         |
| $D_1$        | 159,54 mm | Shoulder diameter on outer ring wide side face    |
| $d_1$        | 137,14 mm | Shoulder diameter on inner ring wide side face    |
| $a$          | 84,4 mm   | Distance between the apexes of the pressure cones |
| $\alpha$     | 40 °      | Contact angle                                     |

Temperature range

|             |        |                            |
|-------------|--------|----------------------------|
| $T_{\ min}$ | -30 °C | Operating temperature min. |
| $T_{\ max}$ | 150 °C | Operating temperature max. |

Additional information

|             |       |                                                  |
|-------------|-------|--------------------------------------------------|
| Tol (+)     | 12 µm | Tolerance for axial clearance or preload per set |
| $A_{\ min}$ | 32 µm | Axial clearance per set min.                     |

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia