

**FAG****B7036-E-T-P4S-UL**

Spindle bearing

Spindle bearing B70...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, restricted tolerances

Informacje techniczne




Twoja aktualna wersja produktu

Preload	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	280 mm	Outside diameter
B	46 mm	Width
C_r	236.000 N	Basic dynamic load rating, radial
C_{0r}	193.000 N	Basic static load rating, radial
C_{ur}	13.500 N	Fatigue load limit, radial
$n_{G \text{ Grease}}$	4.300 1/min	Limiting speed for grease lubrication
$n_{G \text{ Oil}}$	6.700 1/min	Limiting speed for oil lubrication
$\approx m$	8,639 kg	Masa





Mounting dimensions

d _a	196 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	264 mm	Shoulder diameter outer ring
D _a	H12	
r _a max	2,1 mm	Maximum recess radius
r _{a1} max	1 mm	Maximum recess radius
E _{tk} min	210,9 mm	Minimum diameter injection pitch
E _{tk} max	221,9 mm	Maximum diameter injection pitch
E _{tk1} min	210,9 mm	Minimum diameter injection pitch
E _{tk1} max	221,9 mm	Maximum diameter injection pitch
a	76,6 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
r ₁ min	2,1 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

F_{VL}	2.326 N	Preload force light
F_{VM}	7.493 N	Preload force medium
F_{VH}	15.324 N	Preload force heavy
K_{aEL}	6.760 N	Lift-off force light
K_{aEM}	22.418 N	Lift-off force medium
K_{aEH}	47.204 N	Lift-off force heavy
c_{aL}	429 N/ μ m	Axial rigidity light
c_{aM}	665 N/ μ m	Axial rigidity medium
c_{aH}	888 N/ μ m	Axial rigidity heavy

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia