



FAG

B71917-E-2RSD-T-P4S-UL

Spindle bearing

Spindle bearing B719...-E-2RSD, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Sealing	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	120 mm	Outside diameter
B	18 mm	Width
C _r	44.500 N	Basic dynamic load rating, radial
C _{0r}	31.500 N	Basic static load rating, radial
C _{ur}	3.300 N	Fatigue load limit, radial
n _{G Grease}	10.000 1/min	Limiting speed for grease lubrication
≈m	0,527 kg	Masa



Mounting dimensions

d _a	92 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	114 mm	Shoulder diameter outer ring
D _a	H12	
r _a max	0,6 mm	Maximum recess radius
r _{a1} max	0,6 mm	Maximum recess radius
a	32,9 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
r ₁ min	1,1 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Additional information

F _{V L}	333 N	Preload force light
F _{V M}	1.226 N	Preload force medium
F _{V H}	2.609 N	Preload force heavy
K _{aE L}	968 N	Lift-off force light
K _{aE M}	3.675 N	Lift-off force medium
K _{aE H}	8.074 N	Lift-off force heavy
c _{a L}	184 N/μm	Axial rigidity light
c _{a M}	301 N/μm	Axial rigidity medium
c _{a H}	409 N/μm	Axial rigidity heavy



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne