





FAG

B71932-E-T-P4S-UL

Spindle bearing

Spindle bearing B719...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	220 mm	Outside diameter
B	28 mm	Width
C _r	121.000 N	Basic dynamic load rating, radial
C _{0r}	100.000 N	Basic static load rating, radial
C _{ur}	7.700 N	Fatigue load limit, radial
n _{G Grease}	5.300 1/min	Limiting speed for grease lubrication
n _{G Oil}	8.000 1/min	Limiting speed for oil lubrication
≈m	2,587 kg	Masa



Mounting dimensions

d _a	170 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	209 mm	Shoulder diameter outer ring
D _a	H12	
r _a max	1 mm	Maximum recess radius
r _{a1} max	1 mm	Maximum recess radius
E _{tk} min	179,5 mm	Minimum diameter injection pitch
E _{tk} max	184,7 mm	Maximum diameter injection pitch
E _{tk1} min	179,5 mm	Minimum diameter injection pitch
E _{tk1} max	184,7 mm	Maximum diameter injection pitch
a	58,3 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
r ₁ min	1 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

F_{VL}	1.055 N	Preload force light
F_{VM}	3.579 N	Preload force medium
F_{VH}	7.439 N	Preload force heavy
K_{aEL}	3.062 N	Lift-off force light
K_{aEM}	10.696 N	Lift-off force medium
K_{aEH}	22.899 N	Lift-off force heavy
c_{aL}	341 N/ μ m	Axial rigidity light
c_{aM}	539 N/ μ m	Axial rigidity medium
c_{aH}	725 N/ μ m	Axial rigidity heavy

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia