



FAG

B7222-E-T-P4S-UL

Spindle bearing

Spindle bearing B72...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width
C _r	156.000 N	Basic dynamic load rating, radial
C _{0r}	100.000 N	Basic static load rating, radial
C _{ur}	8.500 N	Fatigue load limit, radial
n _{G Grease}	6.000 1/min	Limiting speed for grease lubrication
n _{G Oil}	9.000 1/min	Limiting speed for oil lubrication
≈m	4,527 kg	Masa



Mounting dimensions

d _a	126,5 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	183,5 mm	Shoulder diameter outer ring
D _a	H12	
r _a max	2,1 mm	Maximum recess radius
r _{a1} max	1 mm	Maximum recess radius
E _{tk} min	139,7 mm	Minimum diameter injection pitch
E _{tk} max	148,7 mm	Maximum diameter injection pitch
E _{tk1} min	139,7 mm	Minimum diameter injection pitch
E _{tk1} max	148,7 mm	Maximum diameter injection pitch
a	55,1 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
r ₁ min	2,1 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

F_{VL}	1.512 N	Preload force light
F_{VM}	4.905 N	Preload force medium
F_{VH}	10.048 N	Preload force heavy
K_{aEL}	4.410 N	Lift-off force light
K_{aEM}	14.777 N	Lift-off force medium
K_{aEH}	31.257 N	Lift-off force heavy
c_{aL}	309 N/μm	Axial rigidity light
c_{aM}	484 N/μm	Axial rigidity medium
c_{aH}	650 N/μm	Axial rigidity heavy

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia