




CSXB020-CO15

Four-point contact bearing

Four point contact bearing, Thin section bearing CSXB, brass sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Cage	YH	Brass sheet metal
Radial internal clearance	PL1	Class PL1, Normal
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	50,8 mm	Bore diameter
D	66,675 mm	Outside diameter
B	7,938 mm	Width
C _r	6.300 N	Basic dynamic load rating, radial
C _{0r}	6.200 N	Basic static load rating, radial
n _G	6.700 1/min	Limiting speed
≈m	70 g	Masa

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
d ₁	56,7 mm	Shoulder diameter inner ring
D ₁	60,8 mm	Shoulder diameter outer ring
α	30 °	Contact angle



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia