


E45-XL-KRR

Radial insert ball bearing

Radial insert ball bearings E...KRR,
cylindrical outer ring, location by eccentric
locking collar, R seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	45 mm	Bore diameter
D	85 mm	Outside diameter
B	42,9 mm	Width
B 1	56,5 mm	Locking collar total width
C r	32.500 N	Basic dynamic load rating, radial
C 0r	20.400 N	Basic static load rating, radial
C ur	970 N	Fatigue load limit, radial
≈m	0,85 kg	Masa

Dimensions

C	22 mm	Width, outer ring
C 2	26,4 mm	Sealing total width
S	21,4 mm	Distance raceway
d 1	57,9 mm	Rib diameter inner ring
D 1	72,3 mm	Outside diameter seal
d 3	63 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats

Calculation factors

f 0	14,1	Calculation factor
-----	------	--------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne