




E50-XL-KRR-B-2C

Radial insert ball bearing

Radial insert ball bearings E...KRR-B, spherical outer ring, location by eccentric locking collar, R seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Flinger shields	2C	Flinger shield on both sides
-----------------	----	------------------------------

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D SP	90 mm	Outside diameter
B	49,2 mm	Width
C 0r	23.200 N	Basic static load rating, radial
B 1	62,8 mm	Locking collar total width
C r	35.000 N	Basic dynamic load rating, radial
≈m	0,99 kg	Masa

Dimensions

C	22 mm	Width, outer ring
C 2	35,6 mm	Sealing total width
S	24,6 mm	Distance raceway
d 1	62,8 mm	Rib diameter inner ring
d 3	69 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats



Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna