




FAG

F625-2Z-HLC

Deep groove ball bearing

Deep groove ball bearing F62...-2Z, single row, with flange, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Logistical code	HLC	-
Cage	JN	Steel sheet metal
Design, bearing outer ring	F	Flange
Sealing	2Z	Non-contact shield on both sides
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance

Main Dimensions & Performance Data

d	5 mm	Bore diameter
D	16 mm	Outside diameter
B	5 mm	Width
C _r	1.740 N	Basic dynamic load rating, radial
C _{0r}	630 N	Basic static load rating, radial
C _{ur}	33 N	Fatigue load limit, radial
n _G	53.000 1/min	Limiting speed
n _{gr}	36.000 1/min	Reference speed
m	5,52 g	Masa



Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
D ₁	12,5 mm	Shoulder diameter outer ring
D ₂	13,8 mm	Caliber diameter outer ring
d ₁	8,55 mm	Shoulder diameter inner ring
d ₂	7,5 mm	Caliber diameter inner ring
B _f	1 mm	Width flange
D _f	18 mm	Outer diameter flange

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

f ₀	11,7	Calculation factor
----------------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne