


GE140-AX

Spherical plain bearing

Axial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel

Informacje techniczne



Twoja aktualna wersja produktu

Maintenance	Maintenance required	
Coating	Durotect M	Inner- and outer ring coated with Durotect M (Manganese Phosphate)

Main Dimensions & Performance Data

d	140 mm	Inner diameter bearing
D	260 mm	Outside diameter bearing
T	72 mm	Height
C _a	2.120.000 N	Basic dynamic load rating, axial
C _{0a}	8.170.000 N	Basic static load rating, axial
≈m	18,8 kg	Masa

Mounting dimensions

r _{1smin}	1,5 mm	Edge Spacing
r _{2smin}	0,6 mm	Edge Spacing
d _{a max}	198 mm	Connection measure Inner ring
D _{a min}	187 mm	Housing Connection Diameter



Dimensions

d _K	272 mm	Ball diameter
d ₃	198	Front surface diameter of shaft washer
D ₁	176 mm	Inner diameter of housing washer
B	61 mm	Width Inner ring
C	50 mm	Width Outer ring
s	52,5 mm	Plane Surface Spacing
A	23 mm	Distance lubrication Bore
α	6 °	Tilt angle
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,025 mm	Bore diameter bearing, lower tolerance
D _{OT}	0 mm	Outer diameter, upper tolerance
D _{UT}	-0,035 mm	Outside diameter, lower tolerance
T _{OT}	0 mm	Height, upper tolerance
T _{UT}	-0,5 mm	Height, lower tolerance
C _{UT}	0 mm	Width outer ring, upper tolerance
C _{OT}	-0,5 mm	Width outer ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	-0,5 mm	Width inner ring, lower tolerance
d ₂	244 mm	Connection measure Inner ring

Temperature range

T _{min}	-60 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna