




GE25-XL-KTT-B-AS2/V

Radial insert ball bearing

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Lubrication hole transposed AS2/V

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D SP	52 mm	Outside diameter
B	34,9 mm	Width
C 0r	7.100 N	Basic static load rating, radial
B 1	44,5 mm	Locking collar total width
C r	13.700 N	Basic dynamic load rating, radial
≈m	0,237 kg	Masa

Dimensions

C	15 mm	Width, outer ring
S	17,5 mm	Distance raceway
d 1	33,82 mm	Rib diameter inner ring
D 1	42,5 mm	Outside diameter seal
C a	3,9 mm	Distance to lubrication hole
d 3	37,5 mm	Outside diameter locking collar/locknut
W	3 mm	Width of flats



Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna